

 **4U**
FORM FACTOR
  **2**
CPU SOCKETS
  **32**
DIMM



AGS-4220

4U Dual Intel CPU Rack Mount GPU Server (barebone)

REFERENCE NUMBERS

- Barebone Package: AGS-4220
- Chassis: ASC-R832U4
- Motherboard: ASB-AX42U2

FEATURES

- **5TH AND 4TH GEN. INTEL® XEON® SCALABLE PROCESSORS**
- **DDR5, 32 x RDIMM / RDIMM-3DS DIMM slots**
- **DUAL 1GB/S LAN SUPPORT (RJ45)**
- **OPTIMIZED AIR COOLING 4U RACKMOUNT CHASSIS**
- **10 X PCIE x 16 EXPANSION SLOTS**



APPLICATIONS

- Transfer AI Training
- AI Fine Tuning
- LLM Training & Inference
- AI Cloud
- GPU Accelerated HPC

DIMENSIONS (L x W x H)	850mm x 438.4mm x 177mm / 33.46 in x 17.26 in x 6.97 in
MOTHERBOARD	PROPRIETARY 430.02mm x 350.27mm / 16.93in x 13.79in (L x W)
CPU	5th and 4th Generation Intel® Xeon® Scalable Processors Intel® Xeon® Platinum / Gold / Silver Processor support up to 350W TDP
SOCKET	2 x LGA 4677 (Socket E)
CHIPSET	Intel C741
MEMORY	32 x DDR5 RDIMM / RDIMM-3DS DDR5 slots RDIMM modules (up to 96GB) RDIMM-3DS modules (up to 256GB) 8-Channel per processor - 16 x DIMMs 1.1V modules, 4800MHz/4400MHz memory speed 5th Gen Intel® Xeon: 5600 MT/s (1DPC) / 4400MT/s (2DPC) 4th Gen Intel® Xeon: 4800 MT/s (1DPC) / 4400MT/s (2DPC)
LAN	2 x 1Gbps Intel LAN ports (I350) 1 x Dedicated management port (BMC)
VIDEO	Integrated Aspeed® AST2600 1920x1200@60Hz, DDR4 SDRAM
STORAGE	8 x 3.5/2.5 inch SATA-3 6Gbps HDD / SSD ports (Front Drive Bays) 2 x U.2 NVMe 2.5 inch PCIe Gen 3 SSD (Front Drive Bays) 2 x M.2 NVMe PCIe Gen3 x4 interface (2280/22110, M-key) - Internal
RAID	Intel® SATA RAID 0/1/10/5 (Software RAID)
EXPANSION SLOTS	10 x PCIe 5.0 x16 slots (Full Height Double width slot) , Maximum 10 Dual Slot PCIe Gen 5 GPU support
FRONT I/O	8 x 3.5/2.5 inch SATA-3 6Gbps HDD / SSD ports (Front Drive Bays) 2 x U.2 NVMe 2.5 inch PCIe Gen 3 SSD (Front Drive Bays) 4 x USB 3.2 Gen1 (USB Type A) 1 x VGA (DB15) 2 x 1Gbps Ethernet ports (RJ45) 1 x Dedicated IPMI Management Port (RJ45 MLAN) 1 x UID button with LED 1 x System Reset Button 2 x HDD / System Fault LEDs 1 x NMI Button
TPM	1 x TPM header with SPI interface Optional TPM 2.0 Module
POWER SUPPLY	4+1 2000W 80+ Platinum redundant power supply
OS COMPATIBILITY	Windows Server 2022 / 2019 (x64) Red Hat Enterprise Linux 9.2 / 9.1 / 9.0 / 8.7 / 8.6 (x64) SUSE Linux Enterprise Server 15SP4 (x64) Ubuntu 22.04.3 / 22.04.2 / 22.04.1 / 22.04 LTS (x64) VMware ESXi 8.0 Update 1 / 7.0 Update 3i Citrix Hypervisor 8.2 LTSR CU1
SYSTEM COOLING	8 x hot plug fans - 80x80x38mm (Max 10,000 rpm with Shock absorber) - Internal 5 x hot plug fans - 80x80x38mm (Chassis rear panel mount)
OPERATING PROPERTIES	Operating temperature: 10°C to 35°C Operating humidity: 8%-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
CONTENTS	1 x full barebone unit* 5 x A/C power cords *GPU, CPU, CPU Cooler, Memory, Storage, and OS are not included in the barebone system
PACKAGE DIMENSIONS	1110mm x 652mm x 350mm / 43.70 in x 25.67 in x 13.78 in

DISCLAIMER

The information presented in this document is for informational purposes only and may contain technical inaccuracies, omissions and typographical errors. The information contained herein is subject to change and may be rendered inaccurate for many reasons, including but not limited to product and specification changes, component and motherboard version changes, new model and/or product releases, product difference between differing manufacturers, software changes, BIOS flashes, firmware upgrades, or this like. InnoVISION assumes no obligation to update or otherwise correct or revise this information. However, InnoVISION reserves the rights to revise this information and to make changes from time to time to the content hereof without obligation of InnoVISION to notify any person of such revision or changes. InnoVISION makes no representations or warranties with respect to the contents hereof and assumes no responsibility for any inaccuracies, errors or omissions that may appear in this information.

Copyright Notice

© Copyright, InnoVISION Multimedia Limited. All rights reserved. The INNO3D®, INNO3D Brutal by Nature Logo, are the registered and/or trademarks of InnoVISION Multimedia Limited in Asia, Europe and / or other countries. NVIDIA®, NVIDIA logo are registered and/or trademarks of NVIDIA Corporation in the United States and other countries. All other trademarks and registered trademarks are the property of their respective owners.